




GIHRK30-DO

Rod end

Hydraulic rod end, with thread clamping device, right hand thread, requiring maintenance, sliding contact surface: steel/ steel, open design

Informacje techniczne



Twoja aktualna wersja produktu

Clampable	Clampable	
Maintenance	Maintenance required	
Lubrication nipple	DIN71412-AM6 (tapered grease nipple)	
Slotted	Slotted, both sides	
Thread Pitch	Right-hand thread	
Sealing	Without	
Radial internal clearance	CN (Group N)	Normal internal clearance
Mounting	Internal thread	

Main Dimensions & Performance Data

C _r	81.000 N	Basic dynamic load rating, radial
C _{0r}	96.800 N	Basic static load rating, radial
d	30 mm	Bore diameter bearing
d ₂	64 mm	Outer eye diameter
l ₄	94 mm	Total length internal thread head
D	47 mm	Outside diameter bearing
B	22 mm	Width inner ring
≈m	0,74 kg	Masa



Dimensions

α	6 °	Tilt angle
C 1	28 mm	Width of the rod end
d K	40,7 mm	Ball diameter
d 3	M22x1,5	Thread size
d 4	32 mm	Shank diameter
d 5	50 mm	Shank diameter, large
d 7	M8x25	Diameter screw clamp
h 1	60 mm	Shank Length Internal thread head
l 3	23 mm	Thread length Internal thread
l 7	30 mm	Distance drilling with/shaft start
d UT	-0,01 mm	Bore diameter bearing, lower tolerance
d T	0,01	Bore diameter bearing, tolerance
d OT	0 mm	Bore diameter bearing, upper tolerance
B UT	-0,12 mm	Width inner ring, lower tolerance
B OT	0 mm	Width inner ring, upper tolerance
M A	32 Nm	Tightening torque
G r	0,025 - 0,1 mm	Radial Clearance
G rmin	0,025 mm	Radial clearance, minimum
G rmax	0,1 mm	Radial clearance, maximum

Mounting dimensions

r 1smin	0,6 mm	Edge Spacing
d 1	34,2 mm	Outer flange diameter inner ring

Temperature range

T min	-60 °C	Operating temperature min.
T max	200 °C	Operating temperature max.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna