




GIL25-UK-2RS

Rod end

Rod end with internal thread, maintenance-free, sliding layer: ELGOGLIDE, DIN ISO 12240-4, dimension series E, type F, inner ring curved surface with hard chromium coating, sealed, left hand thread

Informacje techniczne



Twoja aktualna wersja produktu

Clampable	Not clampable	
Maintenance	Maintenance free	
Lubrication nipple	Cannot be relubricated	
Slotted	No	
Thread Pitch	Left-hand thread	
Type of Seal	2RS	Lip seals on both sides
Mounting	Internal thread	

Main Dimensions & Performance Data

C _r	128.000 N	Basic dynamic load rating, radial
C _{0r}	105.000 N	Basic static load rating, radial
d	25 mm	Bore diameter bearing
d ₂	64 mm	Outer eye diameter
l ₄	126 mm	Total length internal thread head
≈m	0,65 kg	Masa



Dimensions

C 1	17 mm	Width of the rod end
D	42 mm	Outside diameter bearing
B	20 mm	Width inner ring
d K	35,5 mm	Ball diameter
d 3	M24x2	Thread size
d 4	33,5 mm	Shank diameter
d 5	42 mm	Shank diameter, large
h 1	94 mm	Shank Length Internal thread head
α	7 °	Tilt angle
l 3	48 mm	Thread length Internal thread
l 5	12 mm	Length rod end shank
l 7	32 mm	Distance drilling with/shaft start
W	36 mm	Width Across Flat
d UT	-0,01 mm	Bore diameter bearing, lower tolerance
d OT	0 mm	Bore diameter bearing, upper tolerance
B UT	-0,12 mm	Width inner ring, lower tolerance
B OT	0 mm	Width inner ring, upper tolerance
G r	0 - 0,05	Radial Clearance
G rmin	0 mm	Radial clearance, minimum
G rmax	0,05 mm	Radial clearance, maximum

Mounting dimensions

r 1smin	0,6 mm	Edge Spacing
d 1	29,3 mm	Outer flange diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	130 °C	Operating temperature max.



Właściwości



Obciążenie promieniowe



Smarowanie dożywotnie, bezobsługowe



Uszczelnienie dwustronne



Nieosiowość statyczna



Nieosiowość dynamiczna