


**GIR45-UK-2RS** **Rod end**

Rod end with internal thread, maintenance-free, sliding layer: ELGOGLIDE, DIN ISO 12240-4, dimension series E, type F, inner ring curved surface with hard chromium coating, sealed, right hand thread

Informacje techniczne**Twoja aktualna wersja produktu**

Clampable	Not clampable	
Maintenance	Maintenance free	
Lubrication nipple	Cannot be relubricated	
Slotted	No	
Thread Pitch	Right-hand thread	
Type of Seal	2RS	Lip seals on both sides
Mounting	Internal thread	

Main Dimensions & Performance Data

C_r	360.000 N	Basic dynamic load rating, radial
C_{0r}	259.000 N	Basic static load rating, radial
d	45 mm	Bore diameter bearing
d_2	102 mm	Outer eye diameter
l_4	196 mm	Total length internal thread head
$\approx m$	2,7 kg	Masa



Dimensions

C ₁	27 mm	Width of the rod end
D	68 mm	Outside diameter bearing
B	32 mm	Width inner ring
d _K	60 mm	Ball diameter
d ₃	M42x3	Thread size
d ₄	58 mm	Shank diameter
d ₅	70 mm	Shank diameter, large
h ₁	145 mm	Shank Length Internal thread head
α	7 °	Tilt angle
l ₃	65 mm	Thread length Internal thread
l ₅	20 mm	Length rod end shank
l ₇	52 mm	Distance drilling with/shaft start
W	60 mm	Width Across Flat
d _{UT}	-0,012 mm	Bore diameter bearing, lower tolerance
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
B _{UT}	-0,12 mm	Width inner ring, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
G _r	0 - 0,06	Radial Clearance
G _{rmin}	0 mm	Radial clearance, minimum
G _{rmax}	0,06 mm	Radial clearance, maximum

Mounting dimensions

r _{1smin}	0,6 mm	Edge Spacing
d ₁	50,7 mm	Outer flange diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	130 °C	Operating temperature max.



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna