




GK25-DO

Rod end

Hydraulic rod end according to ISO24652 and DIN ISO 12240-4, dimension series E, form S with circular weld end, maintenance required, sliding pair steel/steel, open

Informacje techniczne



Twoja aktualna wersja produktu

Clampable	Not clampable
Maintenance	Maintenance required
Lubrication nipple	DIN71412-AS6 (tapered grease nipple)
Slotted	No
Mounting	Weldable, round

Main Dimensions & Performance Data

C _r	62.800 N	Basic dynamic load rating, radial
C _{0r}	70.800 N	Basic static load rating, radial
d	25 mm	Bore diameter bearing
d ₂	64 mm	Outer eye diameter
l ₆	77 mm	Total length welding head
D	42 mm	Outside diameter bearing
B	20 mm	Width inner ring,
≈m	0,47 kg	Masa



Dimensions

α	7 °	Tilt angle
C ₁	17 mm	Width of the rod end
d _K	35,5 mm	Ball diameter
d ₆	33,5 mm	Welding Shank Diameter
d ₇	4 mm	Centering pin diameter
h ₂	45 mm	Shank Length Welding Head
l ₇	32 mm	Distance drilling with/shaft start
l ₈	4 mm	Chamfer
d _{UT}	-0,01 mm	Bore diameter bearing, lower tolerance
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
B _{UT}	-0,12 mm	Width inner ring, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
G _{rmax}	0,1 mm	Radial clearance, maximum
G _{rmin}	0,037 mm	Radial clearance, minimum
G _r	0,037 - 0,1 mm	Radial Clearance

Mounting dimensions

r _{1smin}	0,6 mm	Edge Spacing
d ₁	29,3 mm	Outer flange diameter inner ring

Temperature range

T _{min}	-60 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna