



IMAGE
COMING SOON



GLE50-XL-KRR-B-2C

Radial insert ball bearing

Radial insert ball bearings GLE...KRR-B,
spherical outer ring, non-locating bearing,
drive slot in inner ring, R seals on both sides

X-life

Informacje techniczne

Twoja aktualna wersja produktu

Flinger shields	2C	Flinger shield on both sides
-----------------	----	------------------------------

Main Dimensions & Performance Data

d	50 mm	Bore diameter
D SP	90 mm	Outside diameter
B	49,2 mm	Width
C 0r	23.200 N	Basic static load rating, radial
C r	37.500 N	Basic dynamic load rating, radial
≈m	0,82 kg	Masa

Dimensions

C	22 mm	Width, outer ring
C 2	35,6 mm	Sealing total width
S	19 mm	Distance raceway
d 1	62,84 mm	Rib diameter inner ring
C a	6,9 mm	Distance to lubrication hole
N	10 mm	Hight retaining slot
b	7 mm	Width retaining slot
	H11	Width retaining slot clearance



Temperature range

T_{min}	-40 °C	Operating temperature min.
T_{max}	180 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne



Nieosiowość statyczna