




GRA104-XL-NPP-B-AS2/V

Radial insert ball bearing

Radial insert ball bearings GRA...NPP-B-AS2/V, spherical outer ring, location by eccentric locking collar, P seals on both sides, inch size bore

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	NPP	Lip seal on both sides
Shape of outer surface	B	
Lubrication hole transposed	AS2/V	AS2/V

Main Dimensions & Performance Data

d	31,75 mm	Bore diameter
d	31,75 mm	Bore diameter, inch
D SP	72 mm	Outside diameter
B 1	39 mm	Locking collar total width
B	25,4 mm	Width
C ur	800 N	Fatigue load limit, radial
C r	25.500 N	Basic dynamic load rating, radial
C 0r	15.300 N	Basic static load rating, radial
≈m	0,504 kg	Masa



Dimensions

C	19 mm	Width, outer ring
S	9,5 mm	Distance raceway
d ₂	44,5 mm	Rib diameter sealing inner ring
C _a	5,6 mm	Distance to lubrication hole
d ₃	51 mm	Outside diameter locking collar/locknut
W	4,762 mm	Width across flats (Inch)

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

f ₀	13,8	Calculation factor
----------------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne
	Nieosiowość statyczna