





GRRY30-VA

Flanged housing unit

Flanged housing unit GRRY..-VA

Informacje techniczne



Twoja aktualna wersja produktu

Material	VA	Stainless Steel
Special material	VA	Corrosion-resistant VA design

Main Dimensions & Performance Data

d	30 mm	Bore diameter
H 2	112,7 mm	Height flange
H	112,7 mm	Height flange
U	24,7 mm	Total height unit
C r	18.700 N	Basic dynamic load rating, radial
C 0r	10.700 N	Basic static load rating, radial
C ur	530 N	Fatigue load limit, radial
C 0r G	5.000 N	Load carrying capacity (housing)
≈m	0,6 kg	Masa

Mounting dimensions

J	90,5 mm	Pitch circle diameter (holes)
N	10,5 mm	Fixing square
n	3	Number of screwing holes



Dimensions

A	9 mm	Height housing
B	38,1 mm	Width
S	2,5 mm	Thickness of flange
V	71 mm	Shoulder diameter housing
d ₃	44 mm	Outside diameter eccentric locking collar

Additional information

1	Number of housings
1	Number of housings 2
FLAN62-MSB-VA	Housing
FLAN62-MSA-VA	Housing (Part 2)
GYE30-KRR-B-VA	Bearing designation

Temperature range

T _{min}	-35 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.