


**GSH20-XL-2RSR-B**

Radial insert ball bearing

Radial insert ball bearings GSH...2RSR-B, spherical outer ring, location by adapter sleeve, RSR seals on both sides

X-life

Informacje techniczne

**Main Dimensions & Performance Data**

D _{SP}	47 mm	Outside diameter
B	15 mm	Width
C _{0r}	6.600 N	Basic static load rating, radial
C _{ur}	365 N	Fatigue load limit, radial
C _r	12.700 N	Basic dynamic load rating, radial
≈m	0,15 kg	Masa

Dimensions

C	14 mm	Width, outer ring
S	7,5 mm	Distance raceway
C _a	4 mm	Distance to lubrication hole
b	5 mm	Width retaining slot
t	5 mm	Hight retaining slot adapter sleeve
d ₃	32 mm	Outside diameter locking collar/locknut

Calculation factors

f ₀	13	Calculation factor
----------------	----	--------------------

Additional informationHUESH.SH20-
ZN-0100-HLA

Adapter sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna