




GSH30-XL-2RSR-B

Radial insert ball bearing

Radial insert ball bearings GSH...2RSR-B, spherical outer ring, location by adapter sleeve, RSR seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

D _{SP}	62 mm	Outside diameter
B	18 mm	Width
C _{0r}	11.300 N	Basic static load rating, radial
C _{ur}	600 N	Fatigue load limit, radial
C _r	18.900 N	Basic dynamic load rating, radial
≈m	0,28 kg	Masa

Dimensions

C	18 mm	Width, outer ring
S	9 mm	Distance raceway
C _a	4,7 mm	Distance to lubrication hole
b	5 mm	Width retaining slot
t	5 mm	Hight retaining slot adapter sleeve
d ₃	45 mm	Outside diameter locking collar/locknut

Calculation factors

f ₀	14	Calculation factor
----------------	----	--------------------

Additional information

HUESH.SH30- ZN-0100-HLA	Adapter sleeve
----------------------------	----------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna