




GSH40-XL-2RSR-B

Radial insert ball bearing

Radial insert ball bearings GSH...2RSR-B, spherical outer ring, location by adapter sleeve, RSR seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

D _{SP}	80 mm	Outside diameter
B	22 mm	Width
C _{0r}	19.800 N	Basic static load rating, radial
C _{ur}	930 N	Fatigue load limit, radial
C _r	29.500 N	Basic dynamic load rating, radial
≈m	0,518 kg	Masa

Dimensions

C	21 mm	Width, outer ring
S	11 mm	Distance raceway
C _a	6,4 mm	Distance to lubrication hole
b	5 mm	Width retaining slot
t	5 mm	Hight retaining slot adapter sleeve
d ₃	58 mm	Outside diameter locking collar/locknut

Calculation factors

f ₀	14,6	Calculation factor
----------------	------	--------------------

Additional information

HUESH.SH40-ZN-0100-HLA	Adapter sleeve
------------------------	----------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna