




GYE35-XL-KRR-B

Radial insert ball bearing

Radial insert ball bearings GYE...KRR-B,
spherical outer ring, location by grub screws,
R seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	35 mm	Bore diameter
D SP	72 mm	Outside diameter
B	42,9 mm	Width
C 0r	15.300 N	Basic static load rating, radial
C ur	650 N	Fatigue load limit, radial
C r	25.500 N	Basic dynamic load rating, radial
≈m	0,44 kg	Masa

Dimensions

C	19 mm	Width, outer ring
C 2	22,5 mm	Sealing total width
S	17,5 mm	Distance raceway
d 1	46,8 mm	Rib diameter inner ring
D 1	60,3 mm	Outside diameter seal
C a	5,6 mm	Distance to lubrication hole
A	6 mm	Distance thread
W	3 mm	Width of flats

Calculation factors

f 0	13,8	Calculation factor
-----	------	--------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna