




GYE45-XL-KRR-B

Radial insert ball bearing

Radial insert ball bearings GYE...KRR-B,
spherical outer ring, location by grub screws,
R seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	45 mm	Bore diameter
D SP	85 mm	Outside diameter
B	49,2 mm	Width
C 0r	20.400 N	Basic static load rating, radial
C ur	680 N	Fatigue load limit, radial
C r	32.500 N	Basic dynamic load rating, radial
≈m	0,67 kg	Masa

Dimensions

C	22 mm	Width, outer ring
C 2	26,4 mm	Sealing total width
S	19 mm	Distance raceway
d 1	57 mm	Rib diameter inner ring
D 1	72,3 mm	Outside diameter seal
C a	6,4 mm	Distance to lubrication hole
A	8 mm	Distance thread
W	4 mm	Width of flats

Calculation factors

f 0	14,1	Calculation factor
-----	------	--------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna