




GYE65-214-XL-KRR-B

Radial insert ball bearing

Radial insert ball bearings GYE...KRR-B,
spherical outer ring, location by grub screws,
R seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	65 mm	Bore diameter
D SP	125 mm	Outside diameter
B	74,6 mm	Width
C 0r	44.000 N	Basic static load rating, radial
C ur	1.870 N	Fatigue load limit, radial
C r	66.000 N	Basic dynamic load rating, radial
≈m	2,14 kg	Masa

Dimensions

C	28 mm	Width, outer ring
C 2	32 mm	Sealing total width
S	30,2 mm	Distance raceway
d 1	85,2 mm	Rib diameter inner ring
D 1	109 mm	Outside diameter seal
C a	8,9 mm	Distance to lubrication hole
A	12,1 mm	Distance thread
W	5 mm	Width of flats

Calculation factors

f 0	14,4	Calculation factor
-----	------	--------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna