




GYE75-XL-KRR-B

Radial insert ball bearing

Radial insert ball bearings GYE...-KRR-B,
spherical outer ring, location by grub screws,
R seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	75 mm	Bore diameter
D SP	130 mm	Outside diameter
B	77,8 mm	Width
C 0r	44.500 N	Basic static load rating, radial
C ur	1.880 N	Fatigue load limit, radial
C r	62.000 N	Basic dynamic load rating, radial
≈m	1,96 kg	Masa

Dimensions

C	28 mm	Width, outer ring
C 2	30,5 mm	Sealing total width
S	33,3 mm	Distance raceway
d 1	90 mm	Rib diameter inner ring
D 1	113 mm	Outside diameter seal
C a	8,5 mm	Distance to lubrication hole
A	12,7 mm	Distance thread
W	5 mm	Width of flats

Calculation factors

f 0	14,6	Calculation factor
-----	------	--------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna