



FAG

HC6002-C-2HRS-TVH-L207-C3>V

Deep groove ball bearing

Deep groove ball bearing HC60...-C-2HRS-TVH, Hybrid bearing, single row, Generation C, seals, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>V	Not marked on bearing
Material Bearing	HC	Hybrid bearing, rolling elements ceramic, bearing rings made of steel
Changed internal design	C	GenerationC
Sealing	2HRS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L207	Low noise high-temperature grease, interchangeable with grease L069
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical



Main Dimensions & Performance Data

d	15 mm	Bore diameter
D	32 mm	Outside diameter
B	9 mm	Width
C _r	6.300 N	Basic dynamic load rating, radial
C _{0r}	2.700 N	Basic static load rating, radial
C _{ur}	139 N	Fatigue load limit, radial
n _G	20.300 1/min	Limiting speed
≈m	0,025 kg	Masa

Mounting dimensions

d _{a min}	17 mm	Minimum diameter shaft shoulder
D _{a max}	30 mm	Maximum diameter of housing shoulder
r _{a max}	0,3 mm	Maximum fillet radius

Dimensions

r _{min}	0,3 mm	Minimum chamfer dimension
D ₁	26,84 mm	Shoulder diameter outer ring
D ₂	28,75 mm	Caliber diameter outer ring
d ₁	20,16 mm	Shoulder diameter inner ring
d ₂	19,18 mm	Caliber diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.

Calculation factors

f ₀	13,2	Calculation factor
----------------	------	--------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Izolowane