




FAG

HC6304-C3

Deep groove ball bearing

Deep groove ball bearing HC63, Hybrid bearing, single row, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |              |                                                                       |
|----------------------------------|--------------|-----------------------------------------------------------------------|
| Material Bearing                 | HC           | Hybrid bearing, rolling elements ceramic, bearing rings made of steel |
| Sealing                          | Without      | Not sealed                                                            |
| Cage                             | JN           | Steel sheet metal                                                     |
| Tolerance class                  | PN           | Normal (ISO 492:2023)                                                 |
| Dimensional / heat stabilization | SN           | Rings dimensional stabilized up to 120°                               |
| Lubricant                        | Without      | Bearing not greased                                                   |
| Radial internal clearance        | C3 (Group 3) | Internal clearance larger than CN                                     |
| Bore type                        | Z            | Cylindrical                                                           |

Main Dimensions & Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 20 mm        | Bore diameter                     |
| D               | 52 mm        | Outside diameter                  |
| B               | 15 mm        | Width                             |
| C <sub>r</sub>  | 19.700 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 10.000 N     | Basic static load rating, radial  |
| C <sub>ur</sub> | 395 N        | Fatigue load limit, radial        |
| n <sub>G</sub>  | 23.800 1/min | Limiting speed                    |
| n <sub>gr</sub> | 15.600 1/min | Reference speed                   |
| m               | 0,146 kg     | Masa                              |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 27 mm  | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 45 mm  | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1,1 mm | Maximum fillet radius                |

### Dimensions

|            |          |                              |
|------------|----------|------------------------------|
| $r_{\min}$ | 1,1 mm   | Minimum chamfer dimension    |
| $D_1$      | 41,95 mm | Shoulder diameter outer ring |
| $D_2$      | 44,4 mm  | Caliber diameter outer ring  |
| $d_1$      | 30,3 mm  | Shoulder diameter inner ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 15,7 | Calculation factor |
|-------|------|--------------------|

### Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Obciążenie osiowe dwukierunkowe   |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |
|  | Izolowane                         |