



FAG

HC6318-2Z-L038-C3

Deep groove ball bearing

Deep groove ball bearing HC63...2Z, Hybrid bearing, single row, shields, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |              |                                                                       |
|----------------------------------|--------------|-----------------------------------------------------------------------|
| Material Bearing                 | HC           | Hybrid bearing, rolling elements ceramic, bearing rings made of steel |
| Type of Seal                     | 2Z           | Non-contact shield on both sides                                      |
| Cage                             | JN           | Steel sheet metal                                                     |
| Tolerance class                  | PN           | Normal (ISO 492:2023)                                                 |
| Dimensional / heat stabilization | S0           | Rings dimensional stabilized up to 150°                               |
| Lubricant                        | L038         | Grease (L038/customer specific)                                       |
| Radial internal clearance        | C3 (Group 3) | Internal clearance larger than CN                                     |
| Bore type                        | Z            | Cylindrical                                                           |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 90 mm       | Bore diameter                     |
| D               | 190 mm      | Outside diameter                  |
| B               | 43 mm       | Width                             |
| C <sub>r</sub>  | 164.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 129.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 4.350 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 5.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 5.500 1/min | Reference speed                   |
| m               | 4,663 kg    | Masa                              |



Mounting dimensions

|             |        |                                      |
|-------------|--------|--------------------------------------|
| $d_{a\min}$ | 104 mm | Minimum diameter shaft shoulder      |
| $D_{a\max}$ | 176 mm | Maximum diameter of housing shoulder |
| $r_{a\max}$ | 2,5 mm | Maximum fillet radius                |

Dimensions

|            |           |                              |
|------------|-----------|------------------------------|
| $r_{\min}$ | 3 mm      | Minimum chamfer dimension    |
| $D_1$      | 157,18 mm | Shoulder diameter outer ring |
| $D_2$      | 160,74 mm | Caliber diameter outer ring  |
| $d_1$      | 123,3 mm  | Shoulder diameter inner ring |

Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -20 °C | Operating temperature min. |
| $T_{\max}$ | 150 °C | Operating temperature max. |

Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 17,6 | Calculation factor |
|-------|------|--------------------|

Właściwości

|                                                                                     |                                     |
|-------------------------------------------------------------------------------------|-------------------------------------|
|  | Obciążenie promieniowe              |
|  | Obciążenie osiowe jednokierunkowe   |
|  | Obciążenie osiowe dwukierunkowe     |
|  | Smarowanie dożywotnie, bezobsługowe |
|  | Smarowanie smarem                   |
|  | Uszczelnienie dwustronne            |
|  | Izolowane                           |