


**FAG****HCM71910-C-2RSD-T-P4S-UL-XL**

High speed spindle bearing

High speed spindle bearing HCM719...-C-2RSD, adjusted, in pairs or sets, contact angle $\alpha = 17^\circ$, with ceramic balls, lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Preload class	L	Preload light
Contact angle	Contact angle 17°	Contact angle 17°
Type of Seal	2RSD	Non-contact sealed on both sides and greased "for life"
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	50 mm	Bore diameter
D	72 mm	Outside diameter
B	12 mm	Width
C_r	12.900 N	Basic dynamic load rating, radial
C_{0r}	6.700 N	Basic static load rating, radial
C_{ur}	540 N	Fatigue load limit, radial
n_G Grease	34.000 1/min	Limiting speed for grease lubrication
$\approx m$	113,41 g	Masa



Mounting dimensions

d_a	55 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	67,5 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a\ max}$	0,6 mm	Maximum recess radius
$r_{a1\ max}$	0,15 mm	Maximum recess radius
a	15,3 mm	Distance between the apexes of the pressure cones

Dimensions

$r_{\ min}$	0,6 mm	Minimum chamfer dimension
$r_{1\ min}$	0,3 mm	Minimum chamfer dimension
α	17 °	Contact angle

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	80 °C	Operating temperature max.

Additional information

$F_{V\ L}$	52 N	Preload force light
$F_{V\ M}$	137 N	Preload force medium
$F_{V\ H}$	288 N	Preload force heavy
$K_{aE\ L}$	151 N	Lift-off force light
$K_{aE\ M}$	408 N	Lift-off force medium
$K_{aE\ H}$	881 N	Lift-off force heavy
$c_{a\ L}$	43 N/μm	Axial rigidity light
$c_{a\ M}$	62 N/μm	Axial rigidity medium
$c_{a\ H}$	84 N/μm	Axial rigidity heavy



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne