




FAG

HCS7026-E-T-P4S-UL

High speed spindle bearing

High speed spindle bearing HCS70...-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, with ceramic balls, lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Preload class	L	Preload light
Contact angle	E	Contact angle 25°
Sealing	2RSD	Non-contact sealed on both sides and greased "for life"
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	200 mm	Outside diameter
B	33 mm	Width
C _r	60.000 N	Basic dynamic load rating, radial
C _{0r}	48.000 N	Basic static load rating, radial
C _{ur}	3.000 N	Fatigue load limit, radial
n _G Grease	11.000 1/min	Limiting speed for grease lubrication
≈m	3,27 kg	Masa



Mounting dimensions

d_a	142 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	189 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a\ max}$	2 mm	Maximum recess radius
$r_{a1\ max}$	1 mm	Maximum recess radius
a	55 mm	Distance between the apexes of the pressure cones

Dimensions

$r_{\ min}$	2 mm	Minimum chamfer dimension
$r_{\ 1\ min}$	2 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	80 °C	Operating temperature max.

Additional information

$F_{\ V\ L}$	244 N	Preload force light
$F_{\ V\ M}$	733 N	Preload force medium
$F_{\ V\ H}$	1.466 N	Preload force heavy
$K_{\ aE\ L}$	700 N	Lift-off force light
$K_{\ aE\ M}$	2.126 N	Lift-off force medium
$K_{\ aE\ H}$	4.308 N	Lift-off force heavy
$c_{\ a\ L}$	230 N/μm	Axial rigidity light
$c_{\ a\ M}$	338 N/μm	Axial rigidity medium
$c_{\ a\ H}$	435 N/μm	Axial rigidity heavy



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne