
**HF1216**

## Drawn cup roller clutch

Drawn cup roller clutches HF, with steel springs

## Informacje techniczne



## Twoja aktualna wersja produktu

|                        |          |                                           |
|------------------------|----------|-------------------------------------------|
| Lubricant              | L564     | Grease (L564/standart specific - dynamic) |
| Coating                | Without  |                                           |
| Shape of outer surface | Without  | Smooth outside surface                    |
| Spring design          | Standard | Steel pressure springs                    |

## Main Dimensions &amp; Performance Data

|             |              |                                        |
|-------------|--------------|----------------------------------------|
| $F_w$       | 12 mm        | Under roller diameter                  |
| D           | 18 mm        | Outside diameter                       |
| C           | 16 mm        | Width, outer ring                      |
| $r_{min}$   | 0,3 mm       | Minimum chamfer dimension              |
| $M_{d per}$ | 12,2 Nm      | Permissible torque                     |
| $n_{GW}$    | 11.000 1/min | Limiting speed for rotating shaft      |
| $n_{GA}$    | 8.000 1/min  | Limiting speed for rotating outer ring |
| $\approx m$ | 11,15 g      | Masa                                   |

## Temperature range

|           |        |                            |
|-----------|--------|----------------------------|
| $T_{min}$ | -10 °C | Operating temperature min. |
| $T_{max}$ | 70 °C  | Operating temperature max. |

## Additional information

HK1212

Drawn cup needle roller bearings for radial bearing arrangement



### Właściwości

---



Smarowanie smarem



Bez uszczelnienia



Mala przestrzeń zabudowy



Sprzęgło jednokierunkowe