
**HF1616** **Drawn cup roller clutch**

Drawn cup roller clutches HF, with steel springs

**Informacje techniczne****Twoja aktualna wersja produktu**

|                        |          |                                           |
|------------------------|----------|-------------------------------------------|
| Lubricant              | L564     | Grease (L564/standart specific - dynamic) |
| Coating                | Without  |                                           |
| Shape of outer surface | Without  | Smooth outside surface                    |
| Spring design          | Standard | Steel pressure springs                    |

**Main Dimensions & Performance Data**

|             |             |                                        |
|-------------|-------------|----------------------------------------|
| $F_w$       | 16 mm       | Under roller diameter                  |
| D           | 22 mm       | Outside diameter                       |
| C           | 16 mm       | Width, outer ring                      |
| $r_{min}$   | 0,3 mm      | Minimum chamfer dimension              |
| $M_{d per}$ | 20,5 Nm     | Permissible torque                     |
| $n_{GW}$    | 8.500 1/min | Limiting speed for rotating shaft      |
| $n_{GA}$    | 7.500 1/min | Limiting speed for rotating outer ring |
| $\approx m$ | 15 g        | Masa                                   |

**Temperature range**

|           |        |                            |
|-----------|--------|----------------------------|
| $T_{min}$ | -10 °C | Operating temperature min. |
| $T_{max}$ | 70 °C  | Operating temperature max. |

**Additional information**

HK1612

Drawn cup needle roller bearings for radial bearing arrangement



### Właściwości

---



Smarowanie smarem



Bez uszczelnienia



Mala przestrzeń zabudowy



Sprzęgło jednokierunkowe