


HFL1022

Drawn cup roller clutch

Drawn cup roller clutch HFL, with bearing

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L564	Grease (L564/standart specific - dynamic)
Coating	Without	
Shape of outer surface	Without	Smooth outside surface
Spring design	Standard	Steel pressure springs

Main Dimensions & Performance Data

F_w	10 mm	Under roller diameter
D	14 mm	Outside diameter
C	22 mm	Width, outer ring
C_r	3.950 N	Basic dynamic load rating, radial
C_{0r}	4.500 N	Basic static load rating, radial
r_{min}	0,3 mm	Minimum chamfer dimension
C_{ur}	640 N	Fatigue load limit, radial
n_{GA}	11.000 1/min	Limiting speed for rotating outer ring
n_{GW}	14.000 1/min	Limiting speed for rotating shaft
$\approx m$	7,4 g	Masa

Mounting dimensions

$M_{d\ per}$	5,3 Nm	Permissible torque
--------------	--------	--------------------



Temperature range

T_{min}	-10 °C	Operating temperature min.
T_{max}	70 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Bez uszczelnienia



Mała przestrzeń zabudowy



Sprzęgło jednokierunkowe