


HFL1426

Drawn cup roller clutch

Drawn cup roller clutch HFL, with bearing

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L564	Grease (L564/standart specific - dynamic)
Coating	Without	
Shape of outer surface	Without	Smooth outside surface
Spring design	Standard	Steel pressure springs

Main Dimensions & Performance Data

F_w	14 mm	Under roller diameter
D	20 mm	Outside diameter
C	26 mm	Width, outer ring
C_r	6.800 N	Basic dynamic load rating, radial
C_{0r}	7.800 N	Basic static load rating, radial
r_{min}	0,3 mm	Minimum chamfer dimension
C_{ur}	1.100 N	Fatigue load limit, radial
n_{GA}	8.000 1/min	Limiting speed for rotating outer ring
n_{GW}	9.500 1/min	Limiting speed for rotating shaft
$\approx m$	20,3 g	Masa

Mounting dimensions

$M_{d per}$	17,3 Nm	Permissible torque
-------------	---------	--------------------



Temperature range

T_{min}	-10 °C	Operating temperature min.
T_{max}	70 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Bez uszczelnienia



Mała przestrzeń zabudowy



Sprzęgło jednokierunkowe