
**HK0606** **Drawn cup needle roller bearing open end**

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Informacje techniczne**Twoja aktualna wersja produktu**

Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	6 mm	Under roller diameter
D	10 mm	Outside diameter
C	6 mm	Width
C_r	1.610 N	Basic dynamic load rating, radial
C_{0r}	1.220 N	Basic static load rating, radial
C_{ur}	212 N	Fatigue load limit, radial
n_G	36.500 1/min	Limiting speed
$n_{G \text{ Grease}}$	21.900 1/min	Limiting speed for grease lubrication
n_{gr}	31.500 1/min	Reference speed
m	1,512 g	Masa

Dimensions

C_1	6 mm	Width, outer ring
$r_{\min}$	0,4 mm	Minimum chamfer dimension

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	140 °C	Operating temperature max.



Additional information

GR6X10X2

Sealing ring

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mala przestrzeń zabudowy