



HK1816-B-L271 [🔗](#)

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	Without	
Coating	Without	
Type of Seal	Without	

Main Dimensions & Performance Data

F_w	18 mm	Under roller diameter
D	24 mm	Outside diameter
C	16 mm	Width
C_r	11.600 N	Basic dynamic load rating, radial
C_{0r}	17.300 N	Basic static load rating, radial
C_{ur}	2.180 N	Fatigue load limit, radial
n_G	14.000 1/min	Limiting speed
$n_{G Grease}$	8.400 1/min	Limiting speed for grease lubrication
n_{gr}	10.400 1/min	Reference speed
$\approx m$	15,535 g	Masa

Dimensions

C_1	16 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

SD18X24X3	Sealing ring
G18X24X3	Sealing ring 2
LR15X18X16,5	Suitable inner rings LR
IR15X18X16,5-XL	Suitable inner rings IR

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy