
**HK2218-RS** **Drawn cup needle roller bearing open end**

Drawn cup needle roller bearings with open ends HK...-RS, lip seal on one side, to DIN 618

Informacje techniczne**Twoja aktualna wersja produktu**

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	Without	
Coating	Without	
Type of Seal	RS	Contact seal on one sides

Main Dimensions & Performance Data

F_w	22 mm	Under roller diameter
D	28 mm	Outside diameter
C	18 mm	Width
C_r	13.400 N	Basic dynamic load rating, radial
C_{0r}	22.100 N	Basic static load rating, radial
C_{ur}	2.850 N	Fatigue load limit, radial
n_G	7.000 1/min	Limiting speed
n_{Grease}	7.000 1/min	Limiting speed for grease lubrication
m	22,24 g	Masa

Dimensions

r_{min}	0,8 mm	Minimum chamfer dimension
-----------	--------	---------------------------

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.



Additional information

IR17X22X23-XL

Suitable inner rings IR

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Uszczelnienie jednostronne



Mala przestrzeń zabudowy