


HK2538-ZW

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without	
Number of rows	2	Double-row design

Main Dimensions & Performance Data

F_w	25 mm	Under roller diameter
D	32 mm	Outside diameter
C	38 mm	Width, outer ring
C_r	34.000 N	Basic dynamic load rating, radial
C_{0r}	66.000 N	Basic static load rating, radial
C_{ur}	8.600 N	Fatigue load limit, radial
n_G	10.200 1/min	Limiting speed
n_{gr}	7.300 1/min	Reference speed
m	63,224 g	Masa

Dimensions

r_{min}	0,8 mm	Minimum chamfer dimension
-----------	--------	---------------------------

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	140 °C	Operating temperature max.



Additional information

SD25X32X4	Sealing ring
G25X32X4	Sealing ring 2
LR20X25X38,5	Suitable inner rings LR
IR20X25X38,5-XL	Suitable inner rings IR

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy