


HK2820

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	28 mm	Under roller diameter
D	35 mm	Outside diameter
C	20 mm	Width
C_r	20.900 N	Basic dynamic load rating, radial
C_{0r}	36.000 N	Basic static load rating, radial
C_{ur}	4.700 N	Fatigue load limit, radial
n_G	9.200 1/min	Limiting speed
$n_{G Grease}$	5.500 1/min	Limiting speed for grease lubrication
n_{gr}	6.700 1/min	Reference speed
$\approx m$	36,385 g	Masa

Dimensions

C_1	20 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

SD28X35X4	Sealing ring
G28X35X4	Sealing ring 2
LR22X28X20,5	Suitable inner rings LR
IR22X28X20,5-XL	Suitable inner rings IR

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy