


HK3520-AS1-B

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end
HK...AS1-B, single row, with cage

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without	
Lubrication hole	AS1	With (1)
Coating	Without	
Type of Seal	Without	

Main Dimensions & Performance Data

F_w	35 mm	Under roller diameter
D	42 mm	Outside diameter
C	20 mm	Width
C_r	23.800 N	Basic dynamic load rating, radial
C_{0r}	46.000 N	Basic static load rating, radial
C_{ur}	6.000 N	Fatigue load limit, radial
n_G	7.500 1/min	Limiting speed
$n_{G Grease}$	4.500 1/min	Limiting speed for grease lubrication
n_{gr}	5.500 1/min	Reference speed
$\approx m$	43,988 g	Masa

Dimensions

C_1	20 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

SD35X42X4	Sealing ring
G35X42X4	Sealing ring 2
LR30X35X20,5	Suitable inner rings LR
IR30X35X20,5-XL	Suitable inner rings IR

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Mała przestrzeń zabudowy