
**HK4016**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	40 mm	Under roller diameter
D	47 mm	Outside diameter
C	16 mm	Width
C_r	20.000 N	Basic dynamic load rating, radial
C_{0r}	38.500 N	Basic static load rating, radial
C_{ur}	5.100 N	Fatigue load limit, radial
n_G	6.600 1/min	Limiting speed
$n_{G\text{ Grease}}$	3.950 1/min	Limiting speed for grease lubrication
n_{gr}	5.000 1/min	Reference speed
$\approx m$	39,3 g	Masa

Dimensions

C_1	16 mm	Width, outer ring
$r_{\min}$	0,8 mm	Minimum chamfer dimension



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

SD40X47X4	Sealing ring
G40X47X4	Sealing ring 2
LR35X40X16,5	Suitable inner rings LR
IR35X40X17-XL	Suitable inner rings IR

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Mala przestrzeń zabudowy