






FAG

HSS7008-C-T-P4S-UL

High speed spindle bearing

High speed spindle bearing HSS70...-C, adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Contact angle	C	Contact angle 15°
Type of Seal	2RSD	Non-contact sealed on both sides and greased "for life"
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing
Preload class	L	Preload light
Lubricant	GA21	Grease for super precision bearings, standard

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	68 mm	Outside diameter
B	15 mm	Width
C _r	9.400 N	Basic dynamic load rating, radial
C _{0r}	5.700 N	Basic static load rating, radial
C _{ur}	610 N	Fatigue load limit, radial
n _G Grease	30.000 1/min	Limiting speed for grease lubrication
n _G	45.000 1/min	Limiting speed
≈m	0,209 kg	Masa



Mounting dimensions

d_a	46 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	62 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a\ max}$	1 mm	Maximum recess radius
$r_{a1\ max}$	0,3 mm	Maximum recess radius
a	14,7 mm	Distance between the apexes of the pressure cones

Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$r_{1\ \min}$	1 mm	Minimum chamfer dimension
α	15 °	Contact angle

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	80 °C	Operating temperature max.

Additional information

$F_{V\ L}$	34 N	Preload force light
$F_{V\ M}$	101 N	Preload force medium
$F_{V\ H}$	201 N	Preload force heavy
$K_{aE\ L}$	100 N	Lift-off force light
$K_{aE\ M}$	316 N	Lift-off force medium
$K_{aE\ H}$	659 N	Lift-off force heavy
$c_{a\ L}$	30 N/μm	Axial rigidity light
$c_{a\ M}$	47 N/μm	Axial rigidity medium
$c_{a\ H}$	65 N/μm	Axial rigidity heavy



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne