






FAG

HSS71917-C-T-P4S-UL

High speed spindle bearing

High speed spindle bearing HSS719...-C, adjusted, in pairs or sets, contact angle  $\alpha = 15^\circ$ , lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

|                         |      |                                                                  |
|-------------------------|------|------------------------------------------------------------------|
| Contact angle           | C    | Contact angle $15^\circ$                                         |
| Type of Seal            | 2RSD | Non-contact sealed on both sides and greased "for life"          |
| Cage                    | T    | Laminated fabric cage                                            |
| Tolerance class         | P4S  | Tolerance class P4S, FAG standard better than P4 to ISO 492:2023 |
| Arrangement bearing set | U    | Single bearing                                                   |
| Preload class           | L    | Preload light                                                    |
| Lubricant               | GA21 | Grease for super precision bearings, standard                    |

Main Dimensions & Performance Data

|                       |              |                                       |
|-----------------------|--------------|---------------------------------------|
| d                     | 85 mm        | Bore diameter                         |
| D                     | 120 mm       | Outside diameter                      |
| B                     | 18 mm        | Width                                 |
| C <sub>r</sub>        | 21.200 N     | Basic dynamic load rating, radial     |
| C <sub>0r</sub>       | 17.000 N     | Basic static load rating, radial      |
| C <sub>ur</sub>       | 1.770 N      | Fatigue load limit, radial            |
| n <sub>G</sub> Grease | 15.000 1/min | Limiting speed for grease lubrication |
| n <sub>G</sub>        | 24.000 1/min | Limiting speed                        |
| ≈m                    | 0,62 kg      | Masa                                  |



Mounting dimensions

|                     |         |                                                   |
|---------------------|---------|---------------------------------------------------|
| d <sub>a</sub>      | 92 mm   | Diameter shaft shoulder                           |
| d <sub>a</sub>      | h12     | Diameter shaft shoulder clearance                 |
| D <sub>a</sub>      | 114 mm  | Shoulder diameter outer ring                      |
| D <sub>a</sub>      | H12     | Shoulder diameter outer ring clearance            |
| r <sub>a max</sub>  | 0,6 mm  | Maximum recess radius                             |
| r <sub>a1 max</sub> | 0,6 mm  | Maximum recess radius                             |
| a                   | 22,7 mm | Distance between the apexes of the pressure cones |

Dimensions

|                    |        |                           |
|--------------------|--------|---------------------------|
| r <sub>min</sub>   | 1,1 mm | Minimum chamfer dimension |
| r <sub>1 min</sub> | 1,1 mm | Minimum chamfer dimension |
| α                  | 15 °   | Contact angle             |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 80 °C  | Operating temperature max. |

Additional information

|                   |          |                       |
|-------------------|----------|-----------------------|
| F <sub>V L</sub>  | 74 N     | Preload force light   |
| F <sub>V M</sub>  | 221 N    | Preload force medium  |
| F <sub>V H</sub>  | 442 N    | Preload force heavy   |
| K <sub>aE L</sub> | 220 N    | Lift-off force light  |
| K <sub>aE M</sub> | 689 N    | Lift-off force medium |
| K <sub>aE H</sub> | 1.433 N  | Lift-off force heavy  |
| c <sub>a L</sub>  | 56 N/μm  | Axial rigidity light  |
| c <sub>a M</sub>  | 87 N/μm  | Axial rigidity medium |
| c <sub>a H</sub>  | 119 N/μm | Axial rigidity heavy  |



### Właściwości

---



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne