




K12X18X12-TV

Needle roller cage assembly

Needle roller cage assembly K..-TV, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

Main Dimensions & Performance Data

F _w	12 mm	Inner diameter of needle roller complement
----------------	-------	--

E _w	18 mm	Outside diameter of needle roller complement
----------------	-------	--

B _c	12 mm	Width
----------------	-------	-------

C _r	10.000 N	Basic dynamic load rating, radial
----------------	----------	-----------------------------------

C _{0r}	9.900 N	Basic static load rating, radial
-----------------	---------	----------------------------------

C _{ur}	1.430 N	Fatigue load limit, radial
-----------------	---------	----------------------------

n _G	26.000 1/min	Limiting speed
----------------	--------------	----------------

n _{gr}	18.100 1/min	Reference speed
-----------------	--------------	-----------------

≈m	6,01 g	Masa
----	--------	------

Temperature range

T _{min}	-20 °C	Operating temperature min.
------------------	--------	----------------------------

T _{max}	120 °C	Operating temperature max.
------------------	--------	----------------------------



Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mala przestrzeń zabudowy