




FAG

K1985-1922

Tapered roller bearing

Tapered roller bearings K-Series, in inch sizes, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	ABMA4	Class 4 (ANSI/ABMA 19.2:2013)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	28,575 mm	Bore diameter
D	57,15 mm	Outside diameter
B	19,355 mm	Width, inner ring
C	15,875 mm	Width, outer ring
T	19,845 mm	Width, total
C _r	48.000 N	Basic dynamic load rating, radial
C _{0r}	55.000 N	Basic static load rating, radial
C _{ur}	6.500 N	Fatigue load limit, radial
n _G	13.100 1/min	Limiting speed
n _{gr}	8.400 1/min	Thermal speed rating
≈m	0,229 kg	Masa



Mounting dimensions

d _a max	33,5 mm	Maximum diameter of shaft shoulder
d _b min	34 mm	Minimum diameter of shaft shoulder
D _a min	51 mm	Minimum diameter of housing shoulder
D _a max	50 mm	Maximum diameter of housing shoulder
D _b min	53,5 mm	Minimum diameter of housing shoulder
C _a min	3 mm	Minimum axial space
C _b min	3,8 mm	Minimum axial space
r _a max	0,8 mm	Maximum fillet radius of shaft
r _b max	1,5 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	0,8 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	1,5 mm	Minimum chamfer dimension of outer ring back face
a	13,8 mm	Distance between the apexes of the pressure cones
d ₁	43 mm	Guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,82	Dynamic axial load factor
Y ₀	1	Static axial load factor



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia