

**KBS40-PP-AS**

## Linear Ball Bearing

Linear ball bearings KBS.-PP-AS, machined range, adjustable, sealed on all sides, with relubrication facility, corrosion-resistant design possible

## Informacje techniczne

## Twoja aktualna wersja produktu

|      |    |
|------|----|
| Size | 40 |
|------|----|

## Main Dimensions &amp; Performance Data

|             |          |                     |
|-------------|----------|---------------------|
| $F_w$       | 40 mm    | Bore diameter       |
| D           | 62 mm    | Outside diameter    |
| L           | 80 mm    | Length              |
|             | h12      | Tolerance           |
| $C_{min}$   | 6.000 N  | Load capacity dyn.  |
| $C_{0 min}$ | 4.400 N  | Load capacity stat. |
| $C_{max}$   | 6.400 N  | Load capacity dyn.  |
| $C_{0 max}$ | 5.600 N  | Load capacity stat. |
| $\approx m$ | 0,596 kg | Masa                |

## Mounting dimensions

|          |         |                      |
|----------|---------|----------------------|
| $L_2$    | 60,3 mm |                      |
|          | H13     | Tolerance            |
| $B_{L2}$ | 2,15 mm |                      |
| $B_3$    | 1 mm    |                      |
| $D_N$    | 59 mm   |                      |
| $N_2$    | 3 mm    |                      |
| $\alpha$ | 64 °    |                      |
|          | 6       | Number of rows balls |

