


KGB50-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; sealed, greased, with relubrication facility; corrosion-resistant design possible

Informacje techniczne



Twoja aktualna wersja produktu

Size	50
Seal	PP
Relubrication feature	AS

Technical data

	6	Ball rows
≈m	2,55 kg	Masa

Main Dimensions & Performance Data

F _W	50 mm	Diameter of ball complement
Tol F _W	+ 0,013 mm	Upper tolerance
Tol F _W	- 0,002 mm	Lower tolerance
H	98 mm	Height
L	100 mm	Length
Tol L	h12	Tolerance
B	135 mm	Width
C	8.700 N	Load capacity dyn.
C ₀	6.300 N	Load capacity stat.



Mounting dimensions

J B	116 mm	
Tol J B	+ 0,2 mm	Upper tolerance
Tol J B	- 0,2 mm	Lower tolerance
B 1	96 mm	
A 5	67,5 mm	
Tol A 5	+ 0,02 mm	Upper tolerance
Tol A 5	- 0,02 mm	Lower tolerance
L 4	52 mm	
L 5	72 mm	Length of Shaft Support Block without drive System
J L 4	36 mm	Distance
H 2	50 mm	Center height
Tol H 2	+ 0,015 mm	Upper tolerance
Tol H 2	- 0,015 mm	Lower tolerance
A 3	34 mm	
H 6	14 mm	
N 1	11 mm	
N 3	18 mm	
K 5	M10	
K 8	NIPA2	Lubrication nipple