


KGBA30-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; sealed, greased, with relubrication facility; corrosion-resistant design possible

Informacje techniczne



Twoja aktualna wersja produktu

Size	30
Seal	PP
Relubrication feature	AS

Technical data

	6	Ball rows
≈m	0,62 kg	Masa

Main Dimensions & Performance Data

F _W	30 mm	Diameter of ball complement
Tol F _W	- 0,011 mm	Upper tolerance
Tol F _W	- 0,001 mm	Lower tolerance
H	67 mm	Height
L	68 mm	Length
Tol L	h12	Tolerance
B	84 mm	Width
C	3.600 N	Load capacity dyn. C
C ₀	2.850 N	Load capacity stat. C0



Mounting dimensions

J B	68 mm	
Tol J B	+ 0,2 mm	Upper tolerance
Tol J B	- 0,2 mm	Lower tolerance
A 5	42 mm	
Tol A 5	+ 0,01 mm	Upper tolerance
Tol A 5	- 0,01 mm	Lower tolerance
L 4	60 mm	
L 5	48 mm	
J L	45 mm	
Tol J L	+ 0,2 mm	Upper tolerance
Tol J L	- 0,2 mm	Lower tolerance
H 2	35 mm	Center Height
Tol H 2	+ 0,01 mm	Upper tolerance
Tol H 2	- 0,01 mm	Lower tolerance
A 3	25 mm	
H 6	8,7 mm	
Tol H 6	- 0,5 mm	Tolerance
N 1	6,8 mm	
N 3	11 mm	
K 5	M6	
K 8	NIPA2	Lubrication nipple