**KGB020-PP-AS** **Linear Ball Bearing and Housing Unit**

Linear ball bearing and housing unit; open design, sealed, greased, with relubrication facility; corrosion-resistant design possible

Informacje techniczne**Twoja aktualna wersja produktu**

Seal PP

Relubrication feature AS

Technical data

5 Ball rows

≈m 0,25 kg Masa

Main Dimensions & Performance Data

H 45 mm Center height



L 45 mm Length

Tol L h12 Tolerance

B 70 mm Width

C 1.600 N Load capacity dyn.

C₀ 1.280 N Load capacity stat. C₀





Mounting dimensions

J B	58 mm	
Tol J B	+ 0,15 mm	Upper tolerance
Tol J B	- 0,15 mm	Lower tolerance
B 1	45 mm	
A 5	35 mm	
Tol A 5	+ 0,02 mm	Upper tolerance
Tol A 5	- 0,02 mm	Lower tolerance
B 2	10 mm	
L 4	20 mm	Distance
L 5	28 mm	Distance
J L 4	9,5 mm	Distance
H 2	25 mm	Height shaft
Tol H 2	+ 0,015 mm	Upper tolerance
Tol H 2	- 0,015 mm	Lower tolerance
A 3	21 mm	
H 6	8 mm	
N 1	6,6 mm	
N 3	11 mm	
K 5	M6	
K 8	NIPA1	Lubrication nipple
α	60 °	Angle