




KGSC30-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; with self-aligning linear ball bearing, open design, sealed, greased, with relubrication facility

Informacje techniczne



Twoja aktualna wersja produktu

Size	30
Seal	PP
Relubrication feature	AS

Technical data

	6	Ball rows
≈m	0,95 kg	Masa

Main Dimensions & Performance Data

F _w	30 mm	Diameter of ball complement
H	82 mm	Height
L	68 mm	Length
B	86 mm	Width
C _{max}	5.900 N	Load capacity dyn.
C _{0 max}	6.000 N	Basic static load capacity



Mounting dimensions

A 2	59 mm	
Tol A 2	+ 0,15 mm	Upper tolerance
Tol A 2	- 0,15 mm	Lower tolerance
A 4	76 mm	
A 5	25 mm	Mounting Dimension
Tol A 5	+ 0,01 mm	Upper tolerance
Tol A 5	- 0,01 mm	Lower tolerance
B 2	14,3 mm	Width of sector opening
J L	42 mm	Distance
Tol J L	+ 0,15 mm	Upper tolerance
Tol J L	- 0,15 mm	Lower tolerance
L 6	52 mm	Distance
H 2	40 mm	Center height
Tol H 2	+ 0,008 mm	Upper tolerance
Tol H 2	- 0,016 mm	Lower tolerance
H 4	52 mm	
H 5	9 mm	
T 5	29 mm	
H 6	55,6 mm	
G 2	M16	
N 1	13,5 mm	
N 4	10 mm	
N 3	20 mm	
K 5	M12	
K 8	NIP5MZ	Lubrication nipple
α	57 °	Angle