



FAG

KHH231649-HH231615

Tapered roller bearing

Tapered roller bearings K-Series, in inch sizes, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	ABMA4	Class 4 (ANSI/ABMA 19.2:2013)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	139,7 mm	Bore diameter
D	295,275 mm	Outside diameter
B	87,312 mm	Width, inner ring
C	57,15 mm	Width, outer ring
T	82,55 mm	Width, total
C _r	830.000 N	Basic dynamic load rating, radial
C _{0r}	1.120.000 N	Basic static load rating, radial
C _{ur}	133.000 N	Fatigue load limit, radial
n _G	2.450 1/min	Limiting speed
n _{gr}	1.850 1/min	Thermal speed rating
≈m	24,1 kg	Masa



Mounting dimensions

d _a max	161 mm	Maximum diameter of shaft shoulder
d _b min	177 mm	Minimum diameter of shaft shoulder
D _a min	258 mm	Minimum diameter of housing shoulder
D _b min	263,7 mm	Minimum diameter of housing shoulder
C _a min	9 mm	Minimum axial space
C _b min	19 mm	Minimum axial space
r _a max	9,7 mm	Maximum fillet radius of shaft
r _b max	6,4 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	9,7 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	6,4 mm	Minimum chamfer dimension of outer ring back face
a	56 mm	Distance between the apexes of the pressure cones
d ₁	199,1 mm	Guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,32	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,88	Dynamic axial load factor

Y₀ 1,04 Static axial load factor



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia