




FAG

KHM220149-HM220110

Tapered roller bearing

Tapered roller bearings K-Series, in inch sizes, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	ABMA4	Class 4 (ANSI/ABMA 19.2:2013)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	99,975 mm	Bore diameter
D	156,975 mm	Outside diameter
B	42 mm	Width, inner ring
C	34 mm	Width, outer ring
T	42 mm	Width, total
C _r	250.000 N	Basic dynamic load rating, radial
C _{0r}	410.000 N	Basic static load rating, radial
C _{ur}	49.500 N	Fatigue load limit, radial
n _G	4.250 1/min	Limiting speed
n _{gr}	2.950 1/min	Thermal speed rating
≈m	2,893 kg	Masa



Mounting dimensions

d a max	108 mm	Maximum diameter of shaft shoulder
d b min	122,9 mm	Minimum diameter of shaft shoulder
D a min	142 mm	Minimum diameter of housing shoulder
D a max	146 mm	Maximum diameter of housing shoulder
D b min	151 mm	Minimum diameter of housing shoulder
C a min	5 mm	Minimum axial space
C b min	8 mm	Minimum axial space
r a max	7,9 mm	Maximum fillet radius of shaft
r b max	3,6 mm	Maximum fillet radius of housing

Dimensions

r 1, 2 min	7,9 mm	Minimum chamfer dimension of inner ring back face
r 3, 4 min	3,6 mm	Minimum chamfer dimension of outer ring back face
a	33 mm	Distance between the apexes of the pressure cones
d 1	128,7 mm	Guidance rib diameter of inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,8	Dynamic axial load factor
Y 0	0,99	Static axial load factor



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia