



**KIT.KWSE45-A-OS-230**

Accessory kit, recirculating ball bearing carriage, 6 row

Sealing and lubrication elements KIT for KUSE..

Informacje techniczne



Twoja aktualna wersja produktu

|                               |     |                              |
|-------------------------------|-----|------------------------------|
| Size                          | 45  |                              |
| Suffix code (retrofitability) | OS  | Retrofitting by the customer |
| KIT-number                    | 230 | Kit end number               |

Main Dimensions & Performance Data

|     |          |                    |
|-----|----------|--------------------|
| K 2 | ES 2,2x6 | Screw K2           |
| L S | 3,3 mm   | Dimension screw K1 |
| S   | 0 mm     | Dimension          |
| ≈m  | 33 g     | Masa               |

Degree of contamination

|     |                                                             |
|-----|-------------------------------------------------------------|
| Yes | KIT suitable for very slight degree of contamination        |
| Yes | KIT suitable for very slight degree of contaminationinieren |
| Yes | KIT suitable for moderate degree of contamination           |
| No  | KIT suitable for heavy degree of contamination              |

Related products

|     |                        |
|-----|------------------------|
| Yes | KIT can be retrofitted |
|-----|------------------------|

Increase of displacement

|     |                                         |
|-----|-----------------------------------------|
| Yes | Moderate increase in displacement force |
|-----|-----------------------------------------|

Additional information

|     |                                          |
|-----|------------------------------------------|
| Yes | With closed off upper relubrication hole |
|-----|------------------------------------------|