




KTSOS12-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; open design, adjustable clearance, with self-aligning linear ball bearing, contact seals on both sides

Informacje techniczne



Twoja aktualna wersja produktu


Size	12
Seal	PP
Relubrication feature	AS

Technical data

	6	Ball rows
≈m	0,19 kg	Masa

Main Dimensions & Performance Data

F w	12 mm	Diameter of ball complement
H	28 mm	Height
L	70 mm	Length
B	43 mm	Width
C max	1.460 N	Load capacity dyn.
C 0 max	2.100 N	Load capacity stat.



Mounting dimensions

J B	32 mm	
Tol J B	+ 0,15 mm	Upper tolerance
Tol J B	- 0,15 mm	Lower tolerance
A 5	21,5 mm	
Tol A 5	+ 0,01 mm	Upper tolerance
Tol A 5	- 0,01 mm	Lower tolerance
B 2	7,6 mm	
J L	56 mm	Distance
Tol J L	+ 0,15 mm	Upper tolerance
Tol J L	- 0,15 mm	Lower tolerance
L 6	24 mm	Distance
H 2	18 mm	Center height
Tol H 2	+ 0,008 mm	Upper tolerance
Tol H 2	- 0,016 mm	Lower tolerance
H 5	6,1 mm	
T 5	11 mm	
H 6	16,5 mm	
G 2	M5	
N 1	4,3 mm	
N 4	1,6x3,35	
N 3	8 mm	
K 5	M4	
K 8	NIP4MZ	Lubrication nipple
W	2,5 mm	Width across flats
α	66 °	Angle