




KTSOS16-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; open design, adjustable clearance, with self-aligning linear ball bearing, contact seals on both sides

Informacje techniczne



Twoja aktualna wersja produktu

Size 16

Seal PP

Relubrication feature AS

Technical data

6 Ball rows

≈m 0,31 kg Masa

Main Dimensions & Performance Data

F w 16 mm Diameter of ball complement


H 35 mm Height

L 78 mm Length

B 53 mm Width

C max 2.330 N Load capacity dyn.

C 0 max 3.100 N Load capacity stat.



Mounting dimensions

J B	40 mm	
Tol J B	+ 0,15 mm	Upper tolerance
Tol J B	- 0,15 mm	Lower tolerance
A 5	26,5 mm	
Tol A 5	+ 0,01 mm	Upper tolerance
Tol A 5	- 0,01 mm	Lower tolerance
B 2	10,1 mm	
J L	64 mm	Distance
Tol J L	+ 0,15 mm	Upper tolerance
Tol J L	- 0,15 mm	Lower tolerance
L 6	26 mm	Distance
H 2	22 mm	Center height
Tol H 2	+ 0,008 mm	Upper tolerance
Tol H 2	- 0,016 mm	Lower tolerance
H 5	7,5 mm	
T 5	13 mm	
H 6	21 mm	
G 2	M6	
N 1	5,3 mm	
N 4	1.6x3.35	
N 3	10 mm	
K 5	M5	
K 8	NIP4MZ	Lubrication nipple
W	2,5 mm	Width across flats
α	68 °	Angle