




KTSOS25-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; open design, adjustable clearance, with self-aligning linear ball bearing, contact seals on both sides

Informacje techniczne



Twoja aktualna wersja produktu


Size	25
Seal	PP
Relubrication feature	AS

Technical data

	6	Ball rows
≈m	1,06 kg	Masa

Main Dimensions & Performance Data

F w	25 mm	Diameter of ball complement
H	51 mm	Height
L	122 mm	Length
B	78 mm	Width
C max	6.400 N	Load capacity dyn.
C 0 max	8.600 N	Load capacity stat.



Mounting dimensions

J B	60 mm	
Tol J B	+ 0,15 mm	Upper tolerance
Tol J B	- 0,15 mm	Lower tolerance
A 5	39 mm	
Tol A 5	+ 0,01 mm	Upper tolerance
Tol A 5	- 0,01 mm	Lower tolerance
B 2	12,5 mm	
J L	94 mm	Distance
Tol J L	+ 0,15 mm	Upper tolerance
Tol J L	- 0,15 mm	Lower tolerance
L 6	44 mm	Distance
H 2	30 mm	Center height
Tol H 2	+ 0,008 mm	Upper tolerance
Tol H 2	- 0,016 mm	Lower tolerance
H 5	8,8 mm	
T 5	22 mm	
H 6	29 mm	
G 2	M10	
N 1	8,4 mm	
N 4	2.5x5.3	
N 3	15 mm	
K 5	M8	
K 8	NIP5MZ	Lubrication nipple
W	3 mm	Width across flats
α	57 °	Angle