




KTSOS30-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; open design, adjustable clearance, with self-aligning linear ball bearing, contact seals on both sides

Informacje techniczne



Twoja aktualna wersja produktu

Size 30

Seal PP

Relubrication feature AS

Technical data

6 Ball rows

≈m 1,52 kg Masa

Main Dimensions & Performance Data

F w 30 mm Diameter of ball complement


H 60 mm Height

L 142 mm Length

B 87 mm Width

C max 9.600 N Load capacity dyn.

C 0 max 12.000 N Load capacity stat.



Mounting dimensions

J B	68 mm	
Tol J B	+ 0,15 mm	Upper tolerance
Tol J B	- 0,15 mm	Lower tolerance
A 5	43,5 mm	
Tol A 5	+ 0,01 mm	Upper tolerance
Tol A 5	- 0,01 mm	Lower tolerance
B 2	14,3 mm	
J L	106 mm	Distance
Tol J L	+ 0,15 mm	Upper tolerance
Tol J L	- 0,15 mm	Lower tolerance
L 6	54 mm	Distance
H 2	35 mm	Center height
Tol H 2	+ 0,008 mm	Upper tolerance
Tol H 2	- 0,016 mm	Lower tolerance
H 5	9,7 mm	
T 5	22 mm	
H 6	34 mm	
G 2	M10	
N 1	8,4 mm	
N 4	2.5x5.3	
N 3	15 mm	
K 5	M8	
K 8	NIP5MZ	Lubrication nipple
W	3 mm	Width across flats
α	57 °	Angle