


KWLT20-A-V2-G4

Recirculating ball bearing carriage

Standard flanged carriage, standard end plate,
for four-row linear recirculating ball bearing
and guideway assembly

Informacje techniczne



Twoja aktualna wersja produktu

Size	20	
Carriage design	A	Standard design
Preload class	V2	Preload class 2
Accuracy class	G4	

Main Dimensions & Performance Data

H	30 mm	Height system
B	63 mm	Width carriage
L	71,8 mm	Overall length carriage
C	12.300 N	Dynamic load rating
C ₀	22.400 N	Basic static load capacity
M _{0x}	244 Nm	Static moment rating about X-axis
M _{0y}	173 Nm	Static moment rating about Y-axis
M _{0z}	173 Nm	Static moment rating about Z-axis
M _{0x}	122 Nm	Dynamic moment rating about X-axis
M _{0y}	154 Nm	Dynamic moment rating about y-axis
M _{0z}	154 Nm	Dynamic moment rating about Z-axis
≈m	400 g	Masa



Mounting dimensions

A 1	21,5 mm	Distance from locating edge on carriage to locating edge on guideway
A 2	5 mm	Distance from locating edge to hole
L 1	50 mm	Carrier length
H 1	5 mm	Free space, system dimension
J B	53 mm	Hole spacing
J L	40 mm	Hole Spacing
A 3	5,7 mm	Position lubrication connector
T 5	9 mm	Thread depth
G 2	M6	Thread size, DIN ISO 4762-12.9
G2 M A	16,5 Nm	Maximum tightening torque

Additional information

VMKB_065	KWLT	Material name
----------	------	---------------