


**KWLT25-US-V0-G4**

Recirculating ball bearing carriage

Short & slim carriage, standard end plate, for four-row linear recirculating ball bearing and guideway assembly

Informacje techniczne



Twoja aktualna wersja produktu

|                 |    |                    |
|-----------------|----|--------------------|
| Size            | 25 |                    |
| Carriage design | US | Short, high design |
| Preload class   | V0 | Slight clearance   |
| Accuracy class  | G4 |                    |

Main Dimensions & Performance Data

|                 |          |                                    |
|-----------------|----------|------------------------------------|
| H               | 36 mm    | Height system                      |
| B               | 48 mm    | Width carriage                     |
| L               | 63,6 mm  | Overall length carriage            |
| C               | 14.900 N | Dynamic load rating                |
| C <sub>0</sub>  | 24.300 N | Basic static load capacity         |
| M <sub>0x</sub> | 320 Nm   | Static moment rating about X-axis  |
| M <sub>0y</sub> | 163 Nm   | Static moment rating about Y-axis  |
| M <sub>0z</sub> | 163 Nm   | Static moment rating about Z-axis  |
| M <sub>0x</sub> | 183 Nm   | Dynamic moment rating about X-axis |
| M <sub>0y</sub> | 153 Nm   | Dynamic moment rating about y-axis |
| M <sub>0z</sub> | 153 Nm   | Dynamic moment rating about Z-axis |
| ≈m              | 320 g    | Masa                               |



Mounting dimensions

|        |         |                                                                      |
|--------|---------|----------------------------------------------------------------------|
| A 1    | 12,5 mm | Distance from locating edge on carriage to locating edge on guideway |
| A 2    | 6,5 mm  | Distance from locating edge to hole                                  |
| L 1    | 38,8 mm | Carrier length                                                       |
| H 1    | 7 mm    | Free space, system dimension                                         |
| J B    | 35 mm   | Hole spacing                                                         |
| A 3    | 6,5 mm  | Position lubrication connector                                       |
| T 5    | 6,5 mm  | Thread depth                                                         |
| G 2    | M6      | Thread size, DIN ISO 4762-12.9                                       |
| G2 M A | 16,5 Nm | Maximum tightening torque                                            |

Additional information

|          |      |               |
|----------|------|---------------|
| VMKB_065 | KWLT | Material name |
|----------|------|---------------|