

**KWLT45-HL-V0-G4**

Recirculating ball bearing carriage

Long & high carriage, standard end plate, for four-row linear recirculating ball bearing and guideway assembly

Informacje techniczne

Twoja aktualna wersja produktu

Size	45	
Carriage design	HL	High, long design
Preload class	V0	Slight clearance
Accuracy class	G4	

Main Dimensions & Performance Data

H	70 mm	Height system
B	86 mm	Width carriage
L	167 mm	Overall length carriage
C	72.000 N	Dynamic load rating
C ₀	135.000 N	Basic static load capacity
M _{0x}	3.600 Nm	Static moment rating about X-axis
M _{0y}	2.600 Nm	Static moment rating about Y-axis
M _{0z}	2.600 Nm	Static moment rating about Z-axis
M _{0x}	1.735 Nm	Dynamic moment rating about X-axis
M _{0y}	2.440 Nm	Dynamic moment rating about y-axis
M _{0z}	2.440 Nm	Dynamic moment rating about Z-axis
≈m	3,42 kg	Masa



Mounting dimensions

A 1	20,5 mm	Distance from locating edge on carriage to locating edge on guideway
A 2	13 mm	Distance from locating edge to hole
L 1	128 mm	Carrier length
H 1	14 mm	Free space, system dimension
J B	60 mm	Hole spacing
J L	80 mm	Hole Spacing
A 3	18,5 mm	Position lubrication connector
T 5	20,5 mm	Thread depth
G 2	M10	Thread size, DIN ISO 4762-12.9
G2 M A	81 Nm	Maximum tightening torque

Additional information

VMKB_065	KWLT	Material name
----------	------	---------------