



FAG




N1007-D-K-TVP-SP-XL

Cylindrical roller bearing

Super precision cylindrical roller bearings
N10..-D-K-TVP-SP, non-locating bearing,
with tapered bore, taper 1:12, separable, with
cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TVP	Plastic cage
Tolerance class	SP	Tolerance class SP
Bore type	K	Tapered, taper 1:12
Change mark	D	Internal Variant D
Radial internal clearance	C1 (Group 1)	Internal clearance smaller than C2
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	62 mm	Outside diameter
B	14 mm	Width
C _r	23.600 N	Basic dynamic load rating, radial
C _{0r}	20.900 N	Basic static load rating, radial
C _{ur}	3.350 N	Fatigue load limit, radial
n _{G Grease}	18.700 1/min	Limiting speed for grease lubrication
n _{G Oil}	22.000 1/min	Limiting speed for oil lubrication
≈m	155,01 g	Masa



Mounting dimensions

d_a	43 mm	Diameter shaft shoulder
h_{12}		Diameter shaft shoulder tolerance
D_a	56 mm	Diameter of housing shoulder
H_{12}		Diameter of housing shoulder tolerance
$E_{tk1\text{ nom}}$	53,9 mm	Injection pitch diameter min
$r_{a1\text{ max}}$	0,6 mm	Maximum recess radius

Dimensions

$r_1\text{ min}$	0,6 mm	Minimum chamfer dimension
s_1	2,8 mm	Axial displacement
s_2	2,8 mm	Axial displacement
E	55 mm	Raceway diameter outer ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia